

**Safety Data Sheet**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Issue date: 05/05/2020

Version: 1.0

**SECTION 1: Identification****1.1. Identification**

Product form : Mixture  
Product name : WELD-ON® 4052 Low VOC Multi-Purpose Plastic Pipe Cement

**1.2. Recommended use and restrictions on use**

Use of the substance/mixture : Adhesives, sealants  
Restrictions on use : No additional information available

**1.3. Supplier****Manufacturer**

IPS Corporation  
17109 South Main Street  
Gardena, CA 90248-3127 - USA  
T 310-898-3300  
[www.ipscorp.com](http://www.ipscorp.com)

**Supplier**

IPS Adhesives  
600 Ellis Road  
Durham, NC 27703 - USA  
T 1-919-598-2400

**1.4. Emergency telephone number**

Emergency number : CHEMTEL 800-255-3924 / +1 813-248-0585 (International)

**SECTION 2: Hazard(s) identification****2.1. Classification of the substance or mixture****GHS classification**

Flammable liquids, Category 2  
Serious eye damage/eye irritation, Category 2A  
Carcinogenicity, Category 2  
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation  
Specific target organ toxicity — Single exposure, Category 3, Narcosis

H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H351 Suspected of causing cancer.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.

Full text of H statements : see section 16

**2.2. GHS Label elements, including precautionary statements****GHS-US labelling**

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

H225 - Highly flammable liquid and vapour.  
H319 - Causes serious eye irritation.  
H335 - May cause respiratory irritation.  
H336 - May cause drowsiness or dizziness.  
H351 - Suspected of causing cancer.

Precautionary statements (GHS) :

P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 - Keep container tightly closed.  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical/ventilating/lighting equipment.  
P242 - Use only non-sparking tools.  
P243 - Take precautionary measures against static discharge.  
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P271 - Use only outdoors or in a well-ventilated area.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.

# WELD-ON® 4052 Low VOC Multi-Purpose Plastic Pipe Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P312 - Call a poison center/doctor if you feel unwell  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P370+P378 - In case of fire: Use media other than water to extinguish.  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 - Store in a well-ventilated place. Keep cool.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS\_US)

18.02% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)  
18.02% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)  
18.02% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS classification
Tetrahydrofuran	(CAS-No.) 109-99-9	25 - 45	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H335
2-Butanone	(CAS-No.) 78-93-3	20 - 40	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Cyclohexanone	(CAS-No.) 108-94-1	10 - 20	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332
Silane, dichlorodimethyl-, reaction products with silica	(CAS-No.) 68611-44-9	0 - 2	Acute Tox. 2 (Inhalation:dust,mist), H330
1,2-epoxybutane	(CAS-No.) 106-88-7	0.5 - 1.5	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H335 Aquatic Chronic 3, H412

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
First-aid measures after skin contact : Wash skin thoroughly with mild soap and water. Take off contaminated clothing and wash it before reuse.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects : Suspected of causing cancer.  
Symptoms/effects after inhalation : May cause respiratory irritation. May cause drowsiness or dizziness. Nausea. Headache.  
Symptoms/effects after skin contact : Repeated or prolonged skin contact may cause dermatitis and defatting.  
Symptoms/effects after eye contact : Causes serious eye irritation.  
Symptoms/effects after ingestion : Nausea. Vomiting. Mental confusion.

# WELD-ON® 4052 Low VOC Multi-Purpose Plastic Pipe Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapour. Flammable vapours may accumulate in the container. Heavier than air, vapours may travel long distances along ground, ignite and flash back to source. Thermal decomposition may produce : Carbon oxides (CO, CO<sub>2</sub>), Hydrogen chloride, smoke, Chlorine.

Explosion hazard : May form flammable/explosive vapour-air mixture. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Reactivity : No dangerous reactions known under normal conditions of use.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus. Wear fire/flamm resistant/retardant clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Avoid contact with skin, eyes and clothing. Do not breathe aerosol. Do not breathe vapour. Use personal protective equipment as required.

#### 6.1.1. For non-emergency personnel

Protective equipment : Refer to section 8.2.

Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Refer to section 8.2.

Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters.

### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Use steel container.

Other information : Do not use zinc, aluminum, or plastic containers.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Use only non-sparking tools. Avoid contact with skin, eyes and clothing. Use only outdoors or in a well-ventilated area. Do not breathe aerosol. Do not breathe vapours. Wear personal protective equipment.

Hygiene measures : Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment.

# WELD-ON® 4052 Low VOC Multi-Purpose Plastic Pipe Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Storage conditions	: Keep only in the original container. Keep in fireproof place. Keep container tightly closed.
Incompatible products	: Strong bases. Strong acids. Strong oxidizers. amines. ammonia. Caustic products. Isocyanates.
Incompatible materials	: Sources of ignition. Direct sunlight. Heat sources.
Storage temperature	: 5 – 43 °C
Storage area	: Store in dry, cool, well-ventilated area. Store in a dark area.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Tetrahydrofuran (109-99-9)		
ACGIH	Local name	Tetrahydrofuran
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (ppm)	100 ppm
ACGIH	Remark (ACGIH)	URT irr; CNS impair; kidney dam
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	735 mg/m <sup>3</sup>
NIOSH	NIOSH REL (STEL) (ppm)	250 ppm
2-Butanone (78-93-3)		
ACGIH	Local name	Methyl ethyl ketone (MEK)
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (mg/m <sup>3</sup> )	885 mg/m <sup>3</sup>
ACGIH	ACGIH STEL (ppm)	300 ppm
ACGIH	Remark (ACGIH)	URT irr; CNS & PNS impair
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	885 mg/m <sup>3</sup>
NIOSH	NIOSH REL (STEL) (ppm)	300 ppm
Cyclohexanone (108-94-1)		
ACGIH	Local name	Cyclohexanone
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	50 mg/m <sup>3</sup>
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	50 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
ACGIH	Regulatory reference	ACGIH 2020
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	100 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	25 ppm

# WELD-ON® 4052 Low VOC Multi-Purpose Plastic Pipe Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Silane, dichlorodimethyl-, reaction products with silica (68611-44-9)

Not applicable

### 1,2-epoxybutane (106-88-7)

Not applicable

## 8.2. Appropriate engineering controls

- Appropriate engineering controls : Avoid creating mist or spray. Avoid splashing. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure good ventilation of the work station. Provide local exhaust or general room ventilation.
- Environmental exposure controls : Prevent leakage or spillage.

## 8.3. Individual protection measures/Personal protective equipment

### Personal protective equipment:

Avoid all unnecessary exposure.

#### Hand protection:

Wear suitable gloves resistant to chemical penetration. Butyl rubber gloves

#### Eye protection:

Chemical goggles. If there is a risk of liquid being splashed : face shield

#### Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Approved organic vapour respirator. Appropriate dust or mist respirator should be used if airborne particles are generated when handling this material. In confined space use self-contained breathing apparatus

### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear. Syrupy.
Colour	: Colourless
Odour	: ether
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: > 1
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: > 2
Relative density	: 0.945 – 0.965 @ 23 °C
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

# WELD-ON® 4052 Low VOC Multi-Purpose Plastic Pipe Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 9.2. Other information

VOC content : ≤ 490 g/l

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No dangerous reactions known under normal conditions of use.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

### 10.5. Incompatible materials

Strong bases. Strong acids. Strong oxidizers. amines. ammonia. Caustic products. Isocyanates.

### 10.6. Hazardous decomposition products

None under normal use.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Unknown acute toxicity (GHS_US)	18.02% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 18.02% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 18.02% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))
---------------------------------	--

<b>2-Butanone (78-93-3)</b>	
LD50 oral rat	3460 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
ATE (oral)	3460 mg/kg bodyweight

<b>Cyclohexanone (108-94-1)</b>	
ATE (gases)	4500 ppmv/4h
ATE (vapours)	11 mg/l/4h
ATE (dust,mist)	1.5 mg/l/4h

<b>Silane, dichlorodimethyl-, reaction products with silica (68611-44-9)</b>	
LD50 oral rat	> 5000 mg/kg
LC50 inhalation rat (mg/l)	0.477 mg/l/4h
ATE (vapours)	0.477 mg/l/4h
ATE (dust,mist)	0.477 mg/l/4h

<b>1,2-epoxybutane (106-88-7)</b>	
LD50 oral rat	1100 µl/kg
ATE (oral)	500 mg/kg bodyweight
ATE (dermal)	1100 mg/kg bodyweight
ATE (gases)	4500 ppmv/4h
ATE (vapours)	11 mg/l/4h
ATE (dust,mist)	1.5 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Suspected of causing cancer.

# WELD-ON® 4052 Low VOC Multi-Purpose Plastic Pipe Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Tetrahydrofuran (109-99-9)</b>	
IARC group	2B - Possibly carcinogenic to humans

<b>Cyclohexanone (108-94-1)</b>	
IARC group	3 - Not classifiable

<b>1,2-epoxybutane (106-88-7)</b>	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified  
STOT-single exposure : May cause respiratory irritation. May cause drowsiness or dizziness.

<b>Tetrahydrofuran (109-99-9)</b>	
STOT-single exposure	May cause respiratory irritation.

<b>2-Butanone (78-93-3)</b>	
STOT-single exposure	May cause drowsiness or dizziness.

<b>1,2-epoxybutane (106-88-7)</b>	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified  
Aspiration hazard : Not classified  
Viscosity, kinematic : No data available  
Likely routes of exposure : Inhalation. Skin and eye contact.  
Symptoms/effects : Suspected of causing cancer.  
Symptoms/effects after inhalation : May cause respiratory irritation. May cause drowsiness or dizziness. Nausea. Headache.  
Symptoms/effects after skin contact : Repeated or prolonged skin contact may cause dermatitis and defatting.  
Symptoms/effects after eye contact : Causes serious eye irritation.  
Symptoms/effects after ingestion : Nausea. Vomiting. Mental confusion.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>2-Butanone (78-93-3)</b>	
LC50 fish 1	1587 mg/l
EC50 crustacea	308 mg/l

<b>Silane, dichlorodimethyl-, reaction products with silica (68611-44-9)</b>	
LC50 fish 1	> 10000 mg/l 96 h Brachydanio rerio
EC50 crustacea	> 1000 mg/l 24 h

<b>1,2-epoxybutane (106-88-7)</b>	
LC50 fish 1	> 100 mg/l 96 h
EC50 crustacea	70 mg/l 48 h
ErC50 (algae)	> 500 mg/l 72 h

### 12.2. Persistence and degradability

<b>2-Butanone (78-93-3)</b>	
Persistence and degradability	Readily biodegradable.

<b>1,2-epoxybutane (106-88-7)</b>	
Persistence and degradability	Readily biodegradable.

### 12.3. Bioaccumulative potential

<b>1,2-epoxybutane (106-88-7)</b>	
Log Pow	0.86

### 12.4. Mobility in soil

No additional information available

# WELD-ON® 4052 Low VOC Multi-Purpose Plastic Pipe Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.5. Other adverse effects

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.  
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.  
Additional information : Handle empty containers with care because residual vapours are flammable.  
Ecology - waste materials : Hazardous waste.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1133 ADHESIVES, 3, II  
UN-No.(DOT) : UN1133  
Proper Shipping Name (DOT) : ADHESIVES  
Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120  
Packing group (DOT) : II - Medium Danger  
Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 173  
DOT Packaging Bulk (49 CFR 173.xxx) : 242  
DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packagings may be increased to 5 L (1.3 gallons).  
383 - Packages containing toy plastic or paper caps for toy pistols described as "UN0349, Articles, explosive, n.o.s. (Toy caps), 1.4S" or "NA0337, Toy caps, 1.4S" are not subject to the subpart E (labeling) requirements of this part when offered for transportation by motor vehicle, rail freight, cargo vessel, and cargo aircraft and, notwithstanding the packing method assigned in §173.62 of this subchapter, in conformance with the following conditions:  
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.  
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.  
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)  
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling =  $97 / (1 + a (tr - tf))$  Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.  
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).  
DOT Packaging Exceptions (49 CFR 173.xxx) : 150  
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L  
DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.  
Emergency Response Guide (ERG) Number : 128  
Other information : No supplementary information available.



# WELD-ON® 4052 Low VOC Multi-Purpose Plastic Pipe Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Transport by sea

Transport document description (IMDG)	: UN 1133 ADHESIVES, 3, II
UN-No. (IMDG)	: 1133
Proper Shipping Name (IMDG)	: ADHESIVES
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: II - substances presenting medium danger
Limited quantities (IMDG)	: 5 L

### Air transport

Transport document description (IATA)	: UN 1133 ADHESIVES, 3, II
UN-No. (IATA)	: 1133
Proper Shipping Name (IATA)	: ADHESIVES
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium Danger

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

<b>Tetrahydrofuran (109-99-9)</b>	
Not subject to reporting requirements of the United States SARA Section 313	
CERCLA RQ	1000 lb
<b>2-Butanone (78-93-3)</b>	
Not subject to reporting requirements of the United States SARA Section 313	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	5000 lb
<b>Cyclohexanone (108-94-1)</b>	
Not subject to reporting requirements of the United States SARA Section 313	
CERCLA RQ	5000 lb
<b>1,2-epoxybutane (106-88-7)</b>	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	100 lb

### 15.2. International regulations

#### CANADA

<b>Tetrahydrofuran (109-99-9)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
<b>2-Butanone (78-93-3)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
<b>Cyclohexanone (108-94-1)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
<b>Silane, dichlorodimethyl-, reaction products with silica (68611-44-9)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
<b>1,2-epoxybutane (106-88-7)</b>	
Listed on the Canadian DSL (Domestic Substances List) inventory.	

#### EU-Regulations

No additional information available

<b>Silane, dichlorodimethyl-, reaction products with silica (68611-44-9)</b>	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

# WELD-ON® 4052 Low VOC Multi-Purpose Plastic Pipe Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 1,2-epoxybutane (106-88-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### National regulations

#### Tetrahydrofuran (109-99-9)

Listed on IARC (International Agency for Research on Cancer)

#### Cyclohexanone (108-94-1)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Chinese Catalog of Hazardous Chemicals.  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on KECI (Korean Existing Chemicals Inventory)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the AICS (Australian Inventory of Chemical Substances)

#### Silane, dichlorodimethyl-, reaction products with silica (68611-44-9)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on KECI (Korean Existing Chemicals Inventory)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on Taiwan National Chemical Inventory  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

### 1,2-epoxybutane (106-88-7)

Listed on IARC (International Agency for Research on Cancer)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Chinese Catalog of Hazardous Chemicals.  
Listed on Taiwan National Chemical Inventory  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on KECI (Korean Existing Chemicals Inventory)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on NZIoC (New Zealand Inventory of Chemicals)

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Cyclohexanone(108-94-1)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Tetrahydrofuran(109-99-9)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
2-Butanone(78-93-3)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
1,2-epoxybutane(106-88-7)	U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - Maine - Air Pollutants - Hazardous Air Pollutants; U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances; U.S. - Pennsylvania - RTK (Right to Know) List

## SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Data sources : National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. ACGIH (American Conference of Government Industrial Hygienists). European Standards: Personal Protective Equipment; accessed at: [http://ec.europa.eu/enterprise/policies/european-standards/harmonised-standards/personal-protective-equipment/index\\_en.htm](http://ec.europa.eu/enterprise/policies/european-standards/harmonised-standards/personal-protective-equipment/index_en.htm). OSHA 29CFR 1910.1200 Hazard Communication

# WELD-ON® 4052 Low VOC Multi-Purpose Plastic Pipe Cement

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Standard. Chemical Inspection & Regulation Service; accessed at: [http://www.cirs-reach.com/Inventory/Global\\_Chemical\\_Inventories.html](http://www.cirs-reach.com/Inventory/Global_Chemical_Inventories.html). Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. European Chemicals Agency (ECHA) Registered Substances list. Accessed at <http://echa.europa.eu/>. Manufacturer Information. European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>. TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H-statements:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H412	Harmful to aquatic life with long lasting effects.


Abbreviations and acronyms:

	ACGIH (American Conference of Government Industrial Hygienists)
	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals)
	LD50: Lethal Dose for 50% of the test population
LC50	Median lethal concentration
	TWA: Time Weighted Average
	STEL: Short Term Exposure Limits
VOC	Volatile Organic Compounds

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



**SDS Prepared by:** The Redstone Group, dba SafeBridge Consultants, Inc.  
110 Polaris Pkwy  
Suite 200  
Westerville, OH USA 43082  
P: +1 (614) 923-7472  
[www.redstonegrp.com](http://www.redstonegrp.com)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*