

SECTION 1: Identification**1.1. Identification**

Product form : Mixture
Product name : WELD-ON® 4707 Solvent Cement for ABS

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Adhesives, sealants
Restrictions on use : No additional information available

1.3. Supplier**Manufacturer**

IPS Corporation
17109 South Main Street
Gardena, CA 90248-3127 - USA
T 310-898-3300
www.ipscorp.com

Supplier

IPS Adhesives
600 Ellis Road
Durham, NC 27703 - USA
T 1-919-598-2400

1.4. Emergency telephone number

Emergency number : CHEMTEL 800-255-3924 / +1 813-248-0585 (International)

SECTION 2: Hazard(s) identification**2.1. Classification of the substance or mixture****GHS classification**

Flammable liquids, Category 2
Skin corrosion/irritation, Category 2
Serious eye damage/eye irritation, Category 2A
Specific target organ toxicity — Single exposure, Category 3, Narcosis
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
Full text of H statements : see section 16

H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H335 May cause respiratory irritation.

2.2. GHS Label elements, including precautionary statements**GHS-US labelling**

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS US) :

H225 - Highly flammable liquid and vapour.
H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H335 - May cause respiratory irritation.
H336 - May cause drowsiness or dizziness.

Precautionary statements (GHS) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing mist, spray, vapours.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a poison center/doctor if you feel unwell

WELD-ON® 4707 Solvent Cement for ABS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P321 - Specific treatment (see supplemental first aid instruction on this label).
P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS_US)

40.92% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
40.92% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
40.92% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS classification
2-Butanone	(CAS-No.) 78-93-3	30 - 60	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
2-Propenenitrile, polymer with 1,3-butadiene and ethenylbenzene	(CAS-No.) 9003-56-9	20 - 50	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Acetone	(CAS-No.) 67-64-1	10 - 20	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact : Take off immediately all contaminated clothing. Wash skin thoroughly with mild soap and water. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May cause respiratory irritation. May cause drowsiness or dizziness. In case of over-exposure or in confined areas : Nausea. Headache.
Symptoms/effects after skin contact : Causes skin irritation. Repeated or prolonged skin contact may cause dermatitis and defatting.
Symptoms/effects after eye contact : Causes serious eye irritation. Direct contact may result in corneal injury.
Symptoms/effects after ingestion : Like any product not designed to be ingested, this product may cause stomach distress if ingested in large quantities.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Dry chemical. Foam. Carbon dioxide. Halons. Water fog.

WELD-ON® 4707 Solvent Cement for ABS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Unsuitable extinguishing media : Do not use a heavy water stream. Water spray.

5.2. Specific hazards arising from the chemical

- Fire hazard : Highly flammable liquid and vapour. Flammable vapours may accumulate in the container. Heavier than air, vapours may travel long distances along ground, ignite and flash back to source. Burning produces irritating, toxic and noxious fumes. Carbon oxides (CO, CO₂). smoke.
- Explosion hazard : May form flammable/explosive vapour-air mixture. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
- Reactivity : No dangerous reactions known under normal conditions of use.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment. Fight fire remotely due to the risk of explosion.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear fire/flame resistant/retardant clothing. Positive pressure self-contained breathing apparatus (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Do not breathe aerosol. Do not breathe vapour. Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.

6.1.1. For non-emergency personnel

- Protective equipment : Refer to section 8.2.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Refer to section 8.2.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Put into a labelled container and provide safe disposal.
- Other information : Use steel container. Do not use zinc, aluminum, or plastic containers.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Do not breathe aerosol. Do not breathe vapours. Do not get in eyes, on skin, or on clothing. Do not pierce or burn, even after use. Do not subject to friction, grinding, shock. Wear personal protective equipment. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
- Hygiene measures : Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep only in the original container. Keep in fireproof place. Keep container tightly closed.
- Incompatible products : Caustic products. ammonia. Acids. chlorinated compounds. Strong oxidizers. Isocyanates.
- Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.
- Storage temperature : 5 – 43 °C
- Storage area : Store in dry, cool, well-ventilated area.

WELD-ON® 4707 Solvent Cement for ABS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-Butanone (78-93-3)		
ACGIH	Local name	Methyl ethyl ketone (MEK)
ACGIH	ACGIH TWA (mg/m ³)	590 mg/m ³
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (mg/m ³)	885 mg/m ³
ACGIH	ACGIH STEL (ppm)	300 ppm
ACGIH	Remark (ACGIH)	URT irr; CNS & PNS impair
OSHA	OSHA PEL (TWA) (mg/m ³)	590 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	590 mg/m ³
NIOSH	NIOSH REL TWA [ppm]	200 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	885 mg/m ³
NIOSH	NIOSH REL STEL [ppm]	300 ppm
2-Propenenitrile, polymer with 1,3-butadiene and ethenylbenzene (9003-56-9)		
Not applicable		
Acetone (67-64-1)		
ACGIH	Local name	Acetone
ACGIH	ACGIH TWA (ppm)	250 ppm
ACGIH	ACGIH STEL (ppm)	500 ppm
ACGIH	Remark (ACGIH)	TLV® Basis: URT & eye irr; CNS impair. Notations: A4 (Not classifiable as a Human Carcinogen); BEI
ACGIH	Regulatory reference	ACGIH 2020
OSHA	OSHA PEL (TWA) (mg/m ³)	2400 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-1
NIOSH	NIOSH REL (TWA) (mg/m ³)	590 mg/m ³
NIOSH	NIOSH REL TWA [ppm]	250 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Avoid creating mist or spray. Avoid splashing. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide local exhaust or general room ventilation.

Environmental exposure controls : Prevent leakage or spillage.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration. Butyl rubber gloves

Eye protection:

Chemical goggles. If there is a risk of liquid being splashed : face shield

Skin and body protection:

Rubber Apron

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Approved supplied air respirator. Powered Air-Purifying Respirator (PAPR). An approved organic vapour respirator/supplied air or self-contained breathing apparatus must be used when vapour concentration exceeds applicable exposure limits

WELD-ON® 4707 Solvent Cement for ABS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: milky. Syrupy.
Colour	: No data available
Odour	: ketone
Odour threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butylacetate=1)	: > 1
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: > 2
Relative density	: 0.884 (0.883 – 0.885)
Density	: 7.366 lb/gal
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 3500 – 4500 cP @ 23 °C
Explosive limits	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

VOC content	: ≤ 410 g/l
-------------	-------------

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Highly flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Welding, cutting, heating and brazing.

10.5. Incompatible materials

Strong oxidizers. Acids. Bases. amines. ammonia. Caustic products. Chlorinated solvents. Isocyanates.

10.6. Hazardous decomposition products

None under normal use.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Unknown acute toxicity (GHS_US)	40.92% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 40.92% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
---------------------------------	--

WELD-ON® 4707 Solvent Cement for ABS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	40.92% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))
--	--

2-Butanone (78-93-3)

LD50 oral rat	3460 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
ATE (oral)	3460 mg/kg bodyweight

Acetone (67-64-1)

LD50 oral rat	5800 mg/kg
LD50 dermal rabbit	> 7400 mg/kg
LC50 Inhalation - Rat	76 mg/l/4h
ATE (oral)	5800 mg/kg bodyweight
ATE (vapours)	76 mg/l/4h
ATE (dust,mist)	76 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Acetone (67-64-1)

National Toxicology Program (NTP) Status	Not listed in carcinogenicity class
--	-------------------------------------

Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness. May cause respiratory irritation.

2-Butanone (78-93-3)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

2-Propenenitrile, polymer with 1,3-butadiene and ethenylbenzene (9003-56-9)

STOT-single exposure	May cause respiratory irritation.
----------------------	-----------------------------------

Acetone (67-64-1)

STOT-single exposure	May cause drowsiness or dizziness.
----------------------	------------------------------------

STOT-repeated exposure	: Not classified
------------------------	------------------

Acetone (67-64-1)

LOAEL (oral, rat, 90 days)	11298 mg/kg bodyweight/day
NOAEL (oral, rat, 90 days)	4858 mg/kg bodyweight/day

Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Likely routes of exposure	: Inhalation. Skin and eye contact.
Symptoms/effects after inhalation	: May cause respiratory irritation. May cause drowsiness or dizziness. In case of over-exposure or in confined areas : Nausea. Headache.
Symptoms/effects after skin contact	: Causes skin irritation. Repeated or prolonged skin contact may cause dermatitis and defatting.
Symptoms/effects after eye contact	: Causes serious eye irritation. Direct contact may result in corneal injury.
Symptoms/effects after ingestion	: Like any product not designed to be ingested, this product may cause stomach distress if ingested in large quantities.

SECTION 12: Ecological information

12.1. Toxicity

2-Butanone (78-93-3)

LC50 fish 1	1587 mg/l
EC50 crustacea	308 mg/l

Acetone (67-64-1)

LC50 fish 1	7163 (6210 – 8120) mg/l Pimephales promelas
EC50 crustacea	30806 mg/l
LOEC (chronic)	2212 mg/l

WELD-ON® 4707 Solvent Cement for ABS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetone (67-64-1)

NOEC chronic crustacea > 1106 mg/l

12.2. Persistence and degradability

WELD-ON® 4707 Solvent Cement for ABS

Persistence and degradability Not established.

2-Butanone (78-93-3)

Persistence and degradability Readily biodegradable.

Acetone (67-64-1)

Persistence and degradability Readily biodegradable.

12.3. Bioaccumulative potential

WELD-ON® 4707 Solvent Cement for ABS

Bioaccumulative potential Not established.

Acetone (67-64-1)

Bioconcentration factor (BCF REACH) 3

Bioaccumulative potential Not expected to bioaccumulate.

12.4. Mobility in soil

WELD-ON® 4707 Solvent Cement for ABS

Ecology - soil Not established.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Sewage disposal recommendations : Do not dispose of waste into sewer.
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Handle empty containers with care because residual vapours are flammable.
Ecology - waste materials : Avoid release to the environment. Hazardous waste due to potential risk of fire.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1133 ADHESIVES, 3, II
UN-No.(DOT) : UN1133
Proper Shipping Name (DOT) : ADHESIVES
Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT) : II - Medium Danger
Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packagings may be increased to 5 L (1.3 gallons).
383 - Packages containing toy plastic or paper caps for toy pistols described as "UN0349, Articles, explosive, n.o.s. (Toy caps), 1.4S" or "NA0337, Toy caps, 1.4S" are not subject to the subpart E (labeling) requirements of this part when offered for transportation by motor vehicle, rail freight, cargo vessel, and cargo aircraft and, notwithstanding the packing method assigned in §173.62 of this subchapter, in conformance with the following conditions:
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure

WELD-ON® 4707 Solvent Cement for ABS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

relief devices are authorized on DOT 57 portable tanks.
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

Transport by sea

Transport document description (IMDG) : UN 1133 ADHESIVES, 3, II

UN-No. (IMDG) : 1133

Proper Shipping Name (IMDG) : ADHESIVES

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : II - substances presenting medium danger

Limited quantities (IMDG) : 5 L

Air transport

Transport document description (IATA) : UN 1133 ADHESIVES, 3, II

UN-No. (IATA) : 1133

Proper Shipping Name (IATA) : ADHESIVES

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

2-Butanone (78-93-3)

Not subject to reporting requirements of the United States SARA Section 313

Listed on EPA Hazardous Air Pollutant (HAPS)

Listed on EPA Hazardous Air Pollutant (HAPS)

CERCLA RQ : 5000 lb

2-Propenenitrile, polymer with 1,3-butadiene and ethenylbenzene (9003-56-9)

EPA TSCA Regulatory Flag : XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

Acetone (67-64-1)

CERCLA RQ : 5000 lb

15.2. International regulations

CANADA

2-Butanone (78-93-3)

Listed on the Canadian DSL (Domestic Substances List) inventory.

WELD-ON® 4707 Solvent Cement for ABS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2-Propenenitrile, polymer with 1,3-butadiene and ethenylbenzene (9003-56-9)

Listed on the Canadian DSL (Domestic Substances List) inventory.

Acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

No additional information available

Acetone (67-64-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Acetone (67-64-1)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on Taiwan National Chemical Inventory
Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Chinese Catalog of Hazardous Chemicals.
China Catalogue of Precursors and Chemicals used in Production of Narcotic Drugs and Psychotropic Substances
Listed on KECL/KECI (Korean Existing Chemicals Inventory)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm.

Component	State or local regulations
2-Butanone(78-93-3)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List
Acetone(67-64-1)	U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities; U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date	: 10/02/2020
Data sources	: National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. ACGIH (American Conference of Government Industrial Hygienists). European Standards: Personal Protective Equipment; accessed at: http://ec.europa.eu/enterprise/policies/european-standards/harmonised-standards/personal-protective-equipment/index_en.htm . OSHA 29CFR 1910.1200 Hazard Communication Standard. Chemical Inspection & Regulation Service; accessed at: http://www.cirs-reach.com/Inventory/Global_Chemical_Inventories.html . Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. European Chemicals Agency (ECHA) Registered Substances list. Accessed at http://echa.europa.eu/ . Manufacturer Information. European Chemicals Agency (ECHA) C&L Inventory database. Accessed at http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database . TSCA Chemical Substance Inventory. Accessed at http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html .
Other information	: None.

Full text of H-statements:

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.

Abbreviations and acronyms:

	ACGIH (American Conference of Government Industrial Hygienists)
--	---

WELD-ON® 4707 Solvent Cement for ABS

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	ATE: Acute Toxicity Estimate
	CAS (Chemical Abstracts Service) number
	CLP: Classification, Labelling, Packaging.
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals)
	LD50: Lethal Dose for 50% of the test population
LC50	Median lethal concentration
	TWA: Time Weighted Average
	STEL: Short Term Exposure Limits
	VOC

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Indication of changes:

Product identifier.

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.