

**3061**

Low VOC Thinner for Weld-On 40A Cement

**GENERAL DESCRIPTION**

Weld-On® 3061 is a clear thinner to be used as a reactive diluent for Weld-On 40A only.

**THINNER PROPERTIES AND CHARACTERISTICS @ 73°F (23°C)**

Color:	Clear	VOC Content:	<50 g/l mixed
Viscosity:	Water Thin	Specefic Gravity:	0.944 ± 0.01

**DIRECTIONS FOR USE**

- DO NOT dilute by more than 10% by weight or volume. Excessive dilution may adversely affect cure times or adhesive properties of Weld-On 40.
- Add Weld-On 3061 to mixed Weld-On 40 and stir gently avoiding the introduction of air.
- Let mixture stand for a minute or two allowing air to escape mixture.

**AVAILABILITY**

This product is available in pint (473 ml) metal cans. For detailed information, refer to the current Sign and Display Assembly Selection Guide and Price List.

**SHELF LIFE**

Two years expectancy in tightly sealed containers. Stability of the product is limited by the permanence of the container and the evaporation of the solvent when the container is open.

**QUALITY ASSURANCE**

Weld-On 3061 is carefully evaluated to assure that consistent high quality is maintained. Fourier transform infrared spectroscopy, gas chromatography, and additional in depth testing ensures each batch is manufactured to exacting standards. A batch identification code is stamped on each can and assures traceability of all materials and processes encountered in manufacturing this thinner for its intended specific application.

**SHIPPING**

**Shipping Information for One Liter and Above:** Proper Shipping Name: Methyl Methacrylate Monomer, Stabilized DOT Hazard Class: 3. ID #: UN 1247. Packaging Group: PG II. Label: Class 3 Flammable Liquid. **For Less than One Liter:** DOT Shipping Name: Consumer Commodity. DOT Shipping Class: ORM-D.



## SAFETY AND ENVIRONMENTAL PRECAUTIONS

This product is a flammable, fast evaporating solvent. It is considered a hazardous material. In conformance with the Federal Hazardous Substance Labeling Act, the following hazards and precautions are given. Purchasers who may re-package this product must also conform to all local, state, and federal labeling, safety and other regulations.

**WARNING! EXTREMELY FLAMMABLE. VAPOR HARMFUL.  
MAY BE HARMFUL IF SWALLOWED. MAY IRRITATE SKIN OR EYES.**

Keep out of reach of children. Do not take internally. Keep away from heat, spark, open flame and other sources of ignition. Keep container closed when not in use. Store away from direct sunlight between 40° F – 110° F (5° C – 43° C). Use only in adequate ventilation. Avoid breathing of vapors. Atmospheric levels should be maintained below established exposure limit values contained in Section II and VIII of the Material Safety Data Sheet. If airborne concentrations exceed these limits, use a chemical cartridge respirator or a supplied air respirator. For emergencies and other conditions where short-term exposure may be exceeded use an approved positive pressure self-contained breathing apparatus. In confined areas, use a forced ventilation or NIOSH approved respirator. Do not smoke, eat or drink while working with product. Avoid contact with skin, eyes and clothing. May cause eye injury. Protective equipment such as gloves, safety goggles and impervious apron may be used. Carefully read Material Safety Data Sheet and follow all precautions.

Contains Methyl Methacrylate Monomer (80-62-6). Extent of health risk depends on level and duration of exposure, as well as individual sensitivity. Do not use this product for other than intended use.

“Title III Section 313 Supplier Notification:” This product contains toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40CFR372. This information must be included in all Material Safety Data Sheets that are copied and distributed for this material.

## FIRST AID

**Inhalation:** If overcome with vapors, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call physician.

**Eye Contact:** Flush with plenty of water for 15 minutes. If irritation persists, get medical attention.

**Skin Contact:** Wash skin with plenty of soap and water for at least 15 minutes. If irritation develops, get medical attention.

**Ingestion:** If swallowed, do not induce vomiting. Contact physician immediately.

## IMPORTANT NOTE

This product is intended for use by skilled individuals at their own risk. These suggestions and data are based on information we believe to be reliable. Users should verify by test that this product, as well as these methods, is suited to their application.

## WARRANTY

IPS Corporation (IPS Corp.) warrants that all new IPS Corp. products shall be of good quality and free from defects in material and workmanship for the shelf life as indicated on the product. If any IPS Corp. product becomes defective, or fails to conform to our written limited warranty under normal use and storage conditions, then IPS Corp. will, without charge, replace the nonconforming product. However, this limited warranty shall not extend to, nor shall IPS Corp. be responsible for, damages or loss resulting from accident, misuse, negligent use, improper application, or incorporation of IPS Corp. products into other products. In addition, any repackaging of IPS Corp. products also shall void the limited warranty. IPS Corp. shall not be responsible for, nor does this limited warranty extend to, consequential damage, or incidental damage or expense, including without limitation, injury to persons or property or loss of use. Please refer to our standard IPS Corp. Limited Warranty for additional provisions.

